



## VIDEO CONFERENCING, MEET RADICAL SIMPLICITY

### **BENEFITS**

- Get any small room up and running in minutes, with a simple setup process and all-in-one design
- Make it easy for anyone, even guests, to share content wirelessly from any personal device—with no special apps or tools needed
- Powerful audio pickup and incredible noise blocking technology allows every word to be heard without distractions
- On-board support for cloud service platforms means no room PC or Mac is required

### **POLY STUDIO X30 VIDEO BAR**

Just because your meetings are in small spaces doesn't mean those meetings aren't important.

Meet the Poly Studio X30, an all-in-one video bar for huddle and small rooms. It's radically simple to use with support for leading cloud video services built right in—no PC or Mac required. Voices are crisp and clear, thanks to a beamforming microphone array and acoustic chamber design. Built-in, wireless content sharing lets users share from their devices without the need for cables or pucks. Setup, management, and maintenance are all streamlined, too. Say hello to lower IT costs.

- Ideal for rooms of up to six participants
- Compact, lightweight design easily fits on top or underneath display
- Affordable price delivers excellent huddle room performance without breaking the bank

# POLY STUDIO X30



## SPECIFICATIONS

### PACKAGE INCLUDES:

- Poly Studio X30
- Cable bundle
- Monitor clamp
- Privacy cover

### VIDEO STANDARDS AND PROTOCOLS

- H.264 AVC, H.264 High Profile, H.265

### VIDEO INPUT

- 1x HDMI

### VIDEO OUT

- 1x HDMI
- Touch display compatible

### PEOPLE VIDEO RESOLUTION

- 4K, 30 fps (TX and RX) from 2048 Kbps
- 1080p, 60 fps from 1740 Kbps
- 1080p, 30 fps from 1024 Kbps
- 720p, 60 fps from 832 Kbps
- 720p, 30 fps from 512 Kbps

### CONTENT VIDEO RESOLUTION

- Input
  - UHD (3840 x 2160)
  - HD (1920 x 1080p)
  - WSXGA+ (1680 x 1050)
  - UXGA (1600 x 1200)
  - SXGA (1280 x 1024)
  - WXGA (1280 x 768)
  - HD (1280 x 720p)
  - XGA (1024 x 768)
  - SVGA (800 x 600)

- Output
  - UHD (3840 x 2160)
  - WUXGA (1920 x 1200)
  - HD (1920 x 1080)
  - WSXGA+ (1680 x 1050)
  - SXGA+ (1400 x 1050)
  - SXGA (1280 x 1024)
  - HD (1280 x 720)
  - XGA (1024 x 768)
- Content frame rate
  - 5–60 fps (up to 4K resolution at 15 fps in call)

### CONTENT SHARING

- Poly Content App support
- Apple Airplay
- Miracast
- HDMI input
- Whiteboarding

### CAMERA

- 4x digital zoom
- 120° FOV
- UHD 2160p (4K) capture resolution
- Automatic people framing

### AUDIO INPUT

- Four MEMS microphones

### AUDIO OUTPUT

- Single Speaker

### OTHER INTERFACES

- 1x USB-A (3.0)
- 1x USB-C
- Bluetooth 5.0
- WiFi 802.11a/b/g/n/ac (MIMO) Multi-channel Concurrency

### AUDIO STANDARDS AND PROTOCOLS

- 22 kHz bandwidth with Polycom Siren 22 technology, AAC-LD (TIP calls), G.719
- 14 kHz bandwidth with Polycom Siren 14 technology, G.722.1 Annex C
- 7 kHz bandwidth with G.722, G.722.1
- 3.4 kHz bandwidth with G.711, G.728, G.729A

### NETWORK

- IPv4
- 1x 10/100/1G Ethernet
- Auto-MDIX
- H.323 and/or SIP up to 6 Mbps in Poly App video mode
- Polycom Lost Packet Recovery (LPR) technology
- Dynamic bandwidth allocation
- Reconfigurable MTU size
- Web proxy support—basic, digest, and NTLM
- Simple Certificate Enrollment Protocol (SCEP)

# POLY STUDIO X30



## **SECURITY**

- Media Encryption (H.323, SIP): AES-128, AES-256
- H.235.6 support
- Authenticated access to admin menus, web interface, and APIs
- Local account password policy configuration
- Security profiles
- Local account and login port lockout
- Secure defaults
- Remote logging with support for TLS
- Active directory external authentication

## **OPTIONS**

- VESA and wall mount kit
- Stand
- Poly TC8

## **INTEROPERABILITY**

- Support for native 3rd party applications, including Zoom Rooms for Android
- All cloud service providers through Poly Video App mode

## **ELECTRICAL**

- Auto sensing power supply
- Typical operating voltage/power
  - 37 VA @ 120 V @ 60 Hz
  - 37 VA @ 230 V @ 50/60 Hz
- Typical BTU/h: 65

## **ENVIRONMENTAL SPECIFICATION**

- Operating temperature: 0 to 40 °C
- Operating humidity (non-condensing): 15 to 80%
- Non-operating temperature: -40 to 70 °C
- Non-operating humidity (non-condensing): 5 to 95%
- Maximum altitude: 16,000 ft

## **PHYSICAL CHARACTERISTICS**

- 17.39 W x 2.46 H x 2.42 D (inches)  
441.8 W x 62.5 H x 61.6 D (mm)
- 1.6 lbs/.73 kg

## **WARRANTY**

- One-year return to factory parts and labor

---

\*Some features may only be available with certain native apps or in Poly video mode